



Model no: RZX	Specification	Range	
Hot water powered	Cooling capacity (USRt)	66 ~ 1984	
	Hot water temperature (inlet and outlet)	95°C → 85°C	
	Hot water flow rate (m ³ /h)	25 ~ 750	
	Chilled water temperature (inlet and outlet)	12°C → 7°C	
	Cooling water temperature (inlet and outlet)	30°C → 36°C	
	Electrical data	Power consumption (kW)	2.8 ~ 16.9
		Power supply	3 phase/380V/50 Hz
	Dimension	Length (L)	3420mm ~ 8830mm
		Width (W)	1360mm ~ 3450mm
Height (H)		2210mm ~ 4180mm	
Operating weight (t)		4.2 ~ 67	



Model no: SXZ	Specification	Range	
Steam type	Cooling capacity (USRt)	66 ~ 1984	
	Steam pressure (MPa)	0.4 0.6 0.8	
	Steam consumption (kg/h)	260 ~ 8040	
	Chilled water temperature (inlet and outlet)	12°C → 7°C	
	Cooling water temperature (inlet and outlet)	30°C → 36°C	
	Electrical data	Power consumption (kW)	2.8 ~ 13.2
		Power supply	3 phase/380V/50 Hz
	Dimension	Length (L)	2900mm ~ 9160mm
		Width (W)	1352mm ~ 3590mm
		Height (H)	1960mm ~ 3690mm
Operating weight (t)		3.6 ~ 68.8	



Model no: ZX	Specification	Range	
Direct-fired type	Cooling capacity (USRt)	66 ~ 1984	
	Natural gas consumption (Nm ³ /h)	14.7 ~ 441.2	
	Light oil (kg/h)	14.1 ~ 424.2	
	Chilled water temperature (inlet and outlet)	12°C → 7°C	
	Cooling water temperature (inlet and outlet)	30°C → 36°C	
	Electrical data	Power consumption (kW)	3.2 ~ 34.9
		Power supply	3 phase/380V/50 Hz
	Dimension	Length (L)	2900mm ~ 9610mm
		Width (W)	1680mm ~ 4470mm
Height (H)		1960mm ~ 3690mm	
Operating weight (t)		3.7 ~ 69.5	



Model no: YX	Specification	Range	
Flue gas type / Flue gas + hot water type / Flue gas + hot water + Fuel type	Cooling capacity (USRt)	165 ~ 1984	
	Flue gas temperature (inlet and outlet)	500°C → 170°C	
	Flue gas consumption (Nm ³ /h)	3188 ~ 38250	
	Chilled water temperature (inlet and outlet)	12°C → 7°C	
	Cooling water temperature (inlet and outlet)	30°C → 36°C	
	Electrical data	Power consumption (kW)	2.8 ~ 13.2
		Power supply	3 phase/380V/50 Hz
	Dimension	Length (L)	2980mm ~ 9610mm
		Width (W)	1960mm ~ 4530mm
		Height (H)	2100mm ~ 3745mm
Operating weight (t)		9.2 ~ 70.6	